

YARDMASTER SDS

ABSOLUTE RELIABILITY
ABSOLUTE STABILITY
ZERO DOWNTIME

GALAXY
APPLICATION SPECIFIC, PURPOSE BUILT.

- 3 Stage construction for cushioned ride
- Reinforced tread block to handle extreme stress
- High load carrying capacity and stability
- Presence of special compounds ensuring cut-chip & wear resistance



YARDMASTER SDS



Galaxy Yardmaster SDS adds to YOHT's range of tires for Forklift equipment. The tire completely eliminates breakdown of equipment owing to punctures. Yardmaster SDS is the perfect solution to achieve lowest cost of operation through improved equipment productivity. The steel wire creel beads running across the tire prevents rim slippage and provides improved grip. The presence of special compounds ensures longer tire life.



TIRE PROFILE

- Increases lateral load carrying capacity, stability and traction
- Smooth flat tread reduces wear on hard surfaces
- Large industrial block pattern increases life and provides superior grip
- Wear resistant tread compound provides higher service life.
- Anti slip steel beads provides better rim fitment thus eliminating wheel grip
- Evenly layered compound uniformity that contributes to safety and stability during machine operation
- Fortified sidewall provides protection from sidewall cuts & reduces downtime
- Reinforced strong central tie bar stabilise the machine during extreme stress

3 STAGE CONSTRUCTION



Increased Life:
Tread Rubber

Increased Comfort:
Interior Rubber

Sidewall Protection

Increased Stability:
Base Rubber

Prevents Rim Slippage:
Anti slip steel beads

Size	Rim Code	SH / QH
5.00-8	3.00D-8	SH
		QH*
	3.75-8	SH
		QH*
15X4 1/2-8	3.00D-8	SH
		QH*
16X6-8	4.33R-8	SH
		QH*
18X7-8	4.33R-8	SH
		QH
18X9-8	7.00 -8	SH
		QH
140/55-9	4.00 E - 9	SH
		QH
6.00-9	4.00E - 9	SH
		QH
21X8-9	6.00E - 9	SH
		QH
6.50-10	5.00F-10	SH
		QH
	5.50F-10	SH
		QH
180/60-10	5.00F-10	SH
		QH
7.50-10	5.00F-10	SH
		QH
	5.50F-10	SH
		QH
200/50-10	6.50F-10	SH
		QH
23X9-10	6.50F-10	SH
		QH

Size	Rim Code	SH / QH
7.00-12	5.00S-12	SH
23X10-12	8.00G-12	SH
		QH
27X10-12	8.00G-12	SH
		QH*
315/45-12	10.00G-12	SH
		QH
7.00-15	5.50-15	SH
		QH*
	6.00-15	SH
		QH*
7.50-15	5.50-15	SH
		QH
	6.00-15	SH
		QH
	6.50-15	SH
		QH
8.15-15	7.00-15	SH
		QH
8.25-15	5.50-15	SH
		QH
	6.50-15	SH
		QH
250-15	7.00-15	SH
		QH
	7.50-15	SH
		QH
300-15	8.00-15	SH
		QH

SH – Standard Heel | QH – Quick Heel

Size	Rim Code	SH / QH
355/45-15	9.75-15	SH
355/50-15	9.75-15	SH
		QH
355/65-15	9.75-15	SH
		QH
7.50-16	6.00-16	QH*
		SH
8.25-20	6.50-20	SH
		QH
9.00-20	6.50-20	SH
		QH
	7.00-20	SH
		QH
10.00-20	6.50-20	SH
		QH
	7.00-20 ^#	SH
		QH
10.00-20 (HD)	7.50-20~	SH
		QH*
10.00-20	8.00-20	SH
		QH*
11.00-20	7.50-20	SH
		QH
12.00-20	8.00-20^	SH
		QH
355/50-20	10.00-20	SH
		QH*
12.00-24	8.00-24^	SH
		QH
14.00-24	10.00-24	SH
		QH

*Under Development

- The lip tire(QH) base is profiled for firm seating on the circumferential ridge of the rim
- The one-step tire fitment process ensures faster rim pressing without any hassles

EMAIL: INFO.EUROPE@YOKOHAMA-OHT.COM | WWW.YOKOHAMA-OHT.COM

Haftungsausschluss: Die in diesem Dokument genannten Reifenspezifikationen können sich ohne vorherige Ankündigung ändern. Aktualisierte Informationen und Einzelheiten finden Sie auf unserer Website.

Vertriebshändler:

Mit einer Präsenz in 120 Ländern auf 6 Kontinenten ist ATG auf die Entwicklung, Fertigung und den Vertrieb von Geländereifen spezialisiert. ATG ist eines der am schnellsten wachsenden Unternehmen in dem Segment und verfügt über ein breitgefächertes Angebot bei land- und forstwirtschaftlichen, industriellen und OTR-Reifen und drei weltbekannte Marken - Alliance, Galaxy und Primex. Es ist die Aufgabe von ATG, den Kunden herausragende Werte zu liefern. Wir erreichen dies durch Fokussierung auf Innovation, Technologie und kosteneffiziente Herstellungs- und Vertriebsverfahren. ATG ist eine hundertprozentige Tochterfirma der The Yokohama Rubber Company, Japan.



Alliance Tire Europe BV | De Entree 59, 1101 BH Amsterdam - The Netherlands • Phone: +31 (0) 202 184 770